

BARIX

BARIONET 1000 FAMILY

Universal, programmable I/O device server



The BARIONET 1000 / 1xxx is a Linux/Open-WRT based universal, fully programmable I/O device server. I/O interfaces include two USB host interfaces, WiFi connection, a serial port, analog and digital I/Os, Relays and Dallas 1-wire support - and it is IPv6 capable.

Summary Barionet 1000 family

- USB Host Ports
- Wi-Fi 802.11 b/g/n
- IPv6 capable
- Full user programmable
- Versatile I/O
- Classic Barionet Din-Rail Case
- 2-year warranty
- Developed in Switzerland, manufactured in the EU

Barionet 1100 includes as well

- RS-485
- RTC clock
- Wiegand capability
- Future optional internal interface: LoRa

Specification

- IPv4 / IPv6 stack
 - 16M flash, 64M DRAM
 - One 10/100 Ethernet port
 - Wi-Fi 802.11 b/g/n, 2.4Ghz
 - Two Relay outputs
 - Four open collector (digital) outputs
 - 8 contact closure inputs, 4 of these analogue capable
 - Interface for temperature sensor – Dallas 1-wire 18DS20
 - DB9 RS-232 Serial port
 - Two USB Host ports
 - Supply Voltage 9-30 VDC
-

Technical Specifications

I/O Interface

- Two relay outputs (max. 30 VDC, 5 A)
- Four open collector (digital) outputs (4 x 24 VDC, 0.3 A)
- Eight contact closure inputs (0-15 VDC), four of these are 12 bit analogue inputs (0-15 VDC)
- Universal Dallas 1-Wire® interface for external temperature sensors 18DS20 and other 1-Wire equipment

Serial Interface

- RS-232 (DSub-9 male)
- 600-115'200 baud rate, 7-8 bit, Odd/Even/None Parity

USB Interfaces

- Two USB host ports, can be programmed for different applications

Network Interfaces

- WiFi 802.11 b/g/n, 2.4 GHz
- RJ45 10/100 Mbit auto detect
- IPV4, IPV6 capable
- TCP/IP, UDP, ICMP, DHCP, SNMP, CGI, HTTP web server for control, status and configuration
- LinuQuick auto configuration framework

Status Display

- 11 LED status indicators

Power Supply Input

- 9-30 VDC, 2.5 Watt max.

Case

- High quality plastic, DIN Rail mount
- 4.13" x 3.34" x 1.1", 103mm x 85mm x 31mm

Warranty

- Two years

Environmental

Operating Environment

0 to +50°C / 32 to 122°F

Storage Conditions

0 to +70°C / 32 to 158°F

0 - 70% relative humidity, non-condensing

Certifications/compliant with

CE (A&B), RTT&E, FCC (A&B), RoHS

Ordering Information

2016.9187 Barionet 1000 NoPSU

For commercial related questions (distributors contacts, price list, business opportunities) please contact

sales@barix.com

For technical inquiries (problem reports, request for documentation, etc.) please contact

support@barix.com

Barix AG – Ringstrasse 15A – CH-8600 Dubendorf – info@barix.com – www.barix.com
Phone: +41 43 43322 11

© Barix AG 2016, all rights reserved. All information is subject to change without notice.
All mentioned trademarks belong to their respective owners and are used for reference only. Product sheet V1.0

