

NITE-RF

Unmanaged Industrial Ethernet Switch RJ45
Fast Ethernet



Reliable, space-saving networking in the control cabinet with only 32.5 mm installation depth

- ▶ Flexible use with 24 VAC/VDC
- ▶ Minimal installation depth 32.5 mm
- ▶ Temperature range -40 to +70°C
- ▶ Polarity protection
- ▶ IP30 metal housing
- ▶ Inrush current limitation
- ▶ Stable mounting on 35mm DIN rail
- ▶ PROFINET suitable

Unmanaged Industrial Ethernet Switch RJ45

Fast Ethernet



With an installation depth of only 32.5 mm and a height of 105 mm, the Industrial Ethernet switches impress with their extremely flat and high-quality aluminium housing. The ultra-compact switches can be used in any control cabinet thanks to the 24 VAC/VDC power supply with inrush current limiting and reverse polarity protection. Due to the reduced footprint and the arrangement of all connections on the front, switch cabinets and cabling can be optimized to reduce the costs. The high-quality DIN rail holder made of metal ensures a firm and secure hold on the DIN rail. Like all TERZ Industrial Ethernet switches, the flat NITE-RF are available in two frame forwarding variants and fully suitable for PROFINET applications.

General

Switch: IEEE802.3 Store and Forward; non-blocking wire speed
Auto-Negotiation, Auto-MDI-X, Auto-Polarity: Yes
Frame size: 2,048 Bytes
MAC table size: 2,000 addresses
Quality of Service: Yes – 4 priority queues
Energy Efficient Ethernet: No
Flow Control: No
PROFINET suitable: Yes

Port count (RJ45)	5	8	16
MTBF (SN 29500, Mio. h)	2.709	2.005	1.109
Frame Forwarding (Art.-No.)	xxxxx0	xxxxx1	
LLDP, PTCP Delay 01:80:C2:00:00:0E	Forwarding	Blocking	
RSTP BPDU 01:80:C2:00:00:00	Forwarding	Forwarding	

Power supply / electronics

Nominal voltage: Vin 24 VAC / 24 VDC
Permitted voltage range 5,8 ports: 8 to 28 VAC / 9 to 36 VDC
Permitted voltage range 16 ports: 12 to 28 VAC / 9 to 36 VDC
Connection type: 3-pole pluggable, screw connector (+ - FE)
Wire cross-section: 0,08 to 2,5 (AWG 28 to 12)
Supply circuit: SELV DIN 60950 (circuit breaker 10 A)
Inrush current limiter: Yes
Input fuse: Yes, Interrupting rating 50 A @ 125 VAC / VDC
Polarity protection: Yes
PCB Conformal Coating: No
Protection category: III
Isolation: 0.75 kVDC; Vin ⇔ Ethernet Ports | Vin ⇔ housing

Port count (RJ45)	5	8	16
Power consumption (W)			
Idle full load	0,4 0,9	0,4 1,15	1,9 2,3
Input current (mA)			
Idle full load	16 36	16 48	78 99
Inrush current (A)	8	8	8

Mechanical properties

Housing material: Anodised aluminium, stainless steel
Mounting: 35mm DIN rail
IP Protection class (operation): IP30

Port count (RJ45)	5	8	16
Width (mm)	42	58	110
Height (mm)	105	105	105
Depth (mm)	32,5	32,5	32,5
Weight (g)	205	255	405

Note: We reserve the right to make technical changes to this document without prior notice. TERZ assumes no responsibility or liability for any errors or inaccuracies in this document. All rights to this document and its contents are reserved. Duplication, use of the content or announcement to third parties in any form is not permitted without written permission from TERZ. Copyright © 2018 TERZ Industrial Electronics GmbH. All rights reserved.

Ethernet Interfaces

IEEE Standards: 802.3 10BaseT, 802.3u 100BaseT(X)
Isolation: 0.75 kVDC; Ethernet Port ⇔ housing | Port ⇔ Port
Connection type: RJ45
Port Count | Speed: 5,8 Ports | 10/100 Mbit/s
Cable length: 100 m (Twisted Pair, 0.14 mm² - 0.22 mm², Cat 5)

EMC and environmental specifications

Operating temperature: -40°C to 70°C
Storage temperature: -40°C to 85°C
Relative humidity (operation): 0%-95% (not condensing)
Relative humidity (storage): 0%-95% (not condensing)
Atmospheric pressure (operation): 2,000 m (795 hPa)
EMC immunity: DIN EN - 61000-6-2, 55024
EMC radiated emission: DIN EN 61000-6-4, 55032
Mechanical stability: DIN EN 61373


Approvals and certifications

CE, DIN EN 60950-1

Status and diagnostic indicators

LED: Power | Link/Activity per Port

Drawing



Products

Article	Art.-No.	Specification
NITE-RF5-1100	111400	5xRJ45, IP30, FE, 24 V
NITE-RF8-1100	111600	8xRJ45, IP30, FE, 24 V
NITE-RF16-1100	111800	16xRJ45, IP30, FE, 24 V
NITE-RF5-1101	111401	5xRJ45, IP30, FE, 24 V, LLDP Blocking
NITE-RF8-1101	111601	8xRJ45, IP30, FE, 24 V, LLDP Blocking
NITE-RF16-1101	111801	16xRJ45, IP30, FE, 24 V, LLDP Blocking

Mounting accessories

Adapter for different alignments and wall mounting

TERZ Industrial Electronics GmbH
 Gewerbepark 5a
 D-49143 Bissendorf
 Tel. +495402 60 80 970
 Fax. +495402 60 80 979

070319
 TZDS11140XEA_NITE-RF
 www.terz-ie.com
 info@terz-ie.com

